



Anaheim: 714.999.1616 | Baltimore: 410.584.9099

Test Request Form: MIL-PRF-31032 PCI

NTS Facility Preference: Anaheim, CA Company: Baltimore, MD NTS Quotation Number: Address: Purchase Order: State: Postal Code: City: Date: PO Authorized Signature: Country: Contact: Phone: Email: Part Number: Production Month & Year: Date Code: Lot Number: Serial Numbers: Please indicate the specification sheet samples will be tested to: (defaulted to latest revision/amendment unless otherwise specified) Samples submitted for testing will be tested to the latest MIL-PRF-31032/ Revision Amendment Revision/Amendment. Submission is for DLA monthly/annual retention -or-Submission is for customer retainment only ITAR Requirement: No Board Type: Total Layers: IPC-4101 / Material Type: IPC-4204 / NOTE: Master Drawing must be submitted for all Group B submissions. Evaluations will not be completed until a drawing is supplied. **Periodic Conformance Inspection** PCI Quantity: Periodic Conformance Inspection baseline test coverage (*required tests) Rework Simulation* Submit (2) type 'A' coupons representing the typical component hole or actual production sample. Moisture and Insulation Resistance* & Dielectric Withstanding Voltage Submit (2) type 'E' coupons ("Y" conductor pattern) Resistance to Solvents (optional) Test not required per MIL-PRF-31032. Submit (3) production boards or coupon strips with ink or paint markings. Surface Peel Strength (optional) Surface Peel Quantity: Submit a total of (8) type 'N' or 'P' coupons from a minimum of (2) different production lots (four each from two lots). COPPER SAMPLES ONLY. All surface finish plating or coatings should be chemically removed from specimens prior to test. [Type 3, foil lamination only] Lot #1 ID: Lot #1 s/n(s): Lot #2 ID: Lot #2 s/n(s): Lot #3 ID: Lot #3 s/n(s): Lot #4 ID: Lot #4 s/n(s): Copper Tensile Strength/Elongation Tensile Quantity: Submit (1) sheet of copper per tank. Minimum size of 12" x 12", plated 2-4 mils thick with the tank and vertical direction identified. Tank ID(s): Production Month & Year: Copper Purity(optional) Purity Quantity: Test not required per MIL-PRF-31032. Samples will be taken from the same sheet of copper for tensile/elogation.

Special Test Instructions/Comments:

Flexural Fatigue/Ductility (optional)

Final Test Report:

All final test reports are uploaded to NTS LabInsight for secure customer retrieval. A hard-copy version may be requested at an additional fee.

Hard Copy of Final Test Report Requested

Flexural Quantity:

Test not required per MIL-PRF-31032. Samples will be taken from the same sheet of copper for tensile/elogation.